

ImagePerfect™ 2124 Frontlit Banner is a premium coated banner material featuring excellent thermal welding characteristics and printability. This product has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as latex inks.

## IP 2124

ImagePerfect™ 2124 is a flexible and soft top-quality banner material. It can be used for indoor and outdoor applications such as billboards at trade shows and events, construction sites, show rooms, promotional campaigns and many other applications. IP 2124 offers a high print quality with remarkable text definition and a large colour gamut to ensure colourful images and area in-fills. This product has been UV-stabilized and incorporates an anti-fungus treatment. Thermal welding allows for a strong seam, as does the use of ImagePerfect™ Seam Tack Tape. Laminate: ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	Frontlit banner
COLOUR	White matt
THICKNESS	520μ
WEIGHT	550g/m <sup>2</sup>
TENSILE STRENGTH	2300 / 2100 (N/5cm)
TEAR RESISTENCE	300 / 300 (N)
TEMPERATURE RANGE	-20°C to +70°C
DURABILITY (UNPRINTED)	5 years
FLAME RETARDANCY	(B1)
SHELF LIFE	N/A
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© April 2016 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific features of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.